

12" Sunlight Readable LCD Monitor

LCD-1211VB



- **LED backlight provides longer life, uses less power and provides better color saturation**
- **Ultra-bright technology provides sunlight readability**
- **Mercury and lead free green design**
- **High shock and vibration resistance**
- **On-screen display for: brightness, contrast, back light, hue**
- **Composite, S-Video, PC capability**
- **Low power consumption**
- **Case made of durable steel**
- **Active matrix technology allows wide viewing angle**
- **Front controls for power, menu, up/down**
- **Built-in interface for wall or arm mounting VESA 75mm FPMPI compliant**
- **Response Time: 23ms**

Display: 12.1" TFT LCD active matrix

Back Light: LED

Input Signal: Composite NTSC/PAL (menu select),
S-Video, analog RGB

Pixel Pitch: 0.24(H) x 0.24(V)mm

Resolution: 1024(H) x 768(V)

Display Modes: VGA, SVGA

Brightness rating: 1000 Nit

Contrast Ratio: 700:1

Pixel Configuration: Stripe

Colors: 262,144

Number of Pixels: 786,432

Viewing angle L/R/T/B 70/70/70/70

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Dimensions (WHD): 338 x 278 x 59mm / 13.3" x 10.9" x 2.3"

Actual visible screen size (WH): 246 x 184.5mm / 9.7" x 7.3"

Operating temperature: 32 ~ 122°F or 0 ~ 50°C, 95 % RH

Storage temperature: -4 ~ 140°F or -20 ~ 60°C, 95% RH

Power Requirement: Regulated 12VDC, 5A, negative ground

Part No. DC-1500 required for use in vehicles

Power Consumption: 18.5 W (max)

Includes switching power supply: 110 ~ 240VAC, 5 A / 47 ~ 63Hz

Rear Terminal Connections: Composite BNC video IN/OUT jacks,

S-Video IN jack

PC: 15-pin mini D-sub (female),

Power: 2.1mm DC IN jack

Weight: Net: 3.4 kg. / 7.5 lbs.

Gross: 4.5 kg. / 10 lbs.

Optional Accessories

DC-1500	Factory approved car cord
HM-400	Under-cabinet hinge mount bracket
WM-30	Wall mount bracket (fixed and locking)
WM-31	Wall mount bracket (fixed)
WM-302	Wall mount with swing arm & 4-way
WMC-1015	Ceiling mount